

908.00 EUR
incl. 19% VAT, plus [shipping](#)



- INTEL® Haswell / Broadwell SoC Processor
- 2* DDR3L 1333/1600 up to 16GB
- Support 1 * Serial ATAIII (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- 1 * 24 bits Dual Channel LVDS header
- 1 * mPCIE
- 1 * mSATA (share with mPCIE)
- 2 * USB 2.0 + 4 * USB 3.0
- 2 * HDMI Output
- Supports 2 * Gigabit LAN
- Support CPU Smart FAN
- DC IN Jack 9~24V

| | |
|---------------------|--|
| • Dimension (W*H*D) | • 185 * 60 * 142 mm |
| • Construction | • Aluminum housing |
| • Colors | • Black |
| • MB model | • JNF3E-4300U (3.5 " SBC) |
| • CPU & CHIP | • INTEL® Haswell ULT i5-4300U |
| • BIOS | • AMI 32MB SMT Flash ROM |
| • Memory | • 2 * SO-DIMM (DDR3-1333/1600Mhz_Max 16GB) |
| • Storage Space | • 1 * 2.5" SATA Device (Support SATA 6G / Max Height 9.5 mm) • 1 * m-SATA SSD Device (Mini PCI-E) |
| • Display Interface | • 2 * HDMI • 1 * LVD-24 bits (Internal pin header) |

| | |
|-----------------------|--|
| • Network | <ul style="list-style-type: none"> • 2 * RJ45 (I211AT + I218LM Gigabit LAN) • WiFi (optional / JBC382F3EW-4300UB) |
| • Audio | <ul style="list-style-type: none"> • 1 * Audio |
| • Front I/O Port | <ul style="list-style-type: none"> • 2 * USB 2.0 • 4 * COM |
| • Rear I/O Port | <ul style="list-style-type: none"> • 4 * USB 3.0 • 2 * USB 2.0 |
| • Expansion Interface | <ul style="list-style-type: none"> • 1 * Mini PCI-E (Half-size) |
| • Power Source | <ul style="list-style-type: none"> • DC-12V Jack input • Adapter : AC_90~240V / DC_12V_5A / 60W |
| • Certification | <ul style="list-style-type: none"> • EMC : CE , FCC • Safety : RoHS , ErP |
| • Environment | <ul style="list-style-type: none"> • Operating Temperature : 0 ~ 50■ • Storage Temperature : 0 ~ 60■ • Vibration During Operation : N/A • Shock During Operation : N/A |
| • Mounting | <ul style="list-style-type: none"> • Wall mounting Kits |
| • Packing | <ul style="list-style-type: none"> • Net Weight■2.2KG • Gross Weight■3.5KG • Color Box Dimension■250(W) x 118 (D) x 295 (H) mm |