

498.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- HBFDF20 !



- Intel® Elkhart Lake SoC Processor (Default: J6412)
- Support 1\* DDR4 3200MHz SO-DIMM up to 32GB
- Support 8\* USB, 2\* RJ45, 4\* COM, 2\* HDMI
- All-aluminum body, produced by casting process
- Support DC12~24V input)

Model	<ul style="list-style-type: none"> <li>- HBFDF20-6412-B (Default) / HBFDF20I-6412-B (Default, WiFi)</li> <li>- HBFDF20-6412-T (TPM) / HBFDF20I-6412-T (TPM, WiFi)</li> <li>- HBFDF20-6412-E (32GB EMMC) / HBFDF20I-6412-E (32GB EMMC, WiFi)</li> <li>- HBFDF20-6412-Q (32GB EMMC, TPM) / HBFDF20I-6412-Q (32GB EMMC, TPM, WiFi)</li> </ul>	
Model	<ul style="list-style-type: none"> <li>- MF20-00B (J6412 CPU_10W, Default)</li> <li>- MF20-02B (J6412 CPU_10W, TPM2.0)</li> <li>- MF20-03B (J6412 CPU_10W, EMMC)</li> <li>- MF20-07B (J6412 CPU_10W, 32GB EMMC, TPM2.0)</li> </ul>	
CPU/Chipset	- Intel® Elkhart Lake SoC Processor (Default: J6412, TDP 10W)	
BIOS	- AMI Flash ROM	
Memory	- 1* DDR4 3200MHz SO-DIMM up to 32GB	
Network	- 2* Intel® i225LM 2.5GbE	
Graphics	<ul style="list-style-type: none"> <li>- Intel® HD Graphics, shared memory</li> <li>- 2* HDMI (Max Resolution: 4096x2160@60Hz)</li> </ul>	
Storage	<ul style="list-style-type: none"> <li>- 1* M.2 M-key (2242/2280, PCIe Gen.3 x2/SATA interface) support NVME</li> <li>- 1* 2.5" SATAIII 6Gb/s internal drive bay (Max. Height 9.5 mm)</li> <li>- 32GB eMMC onboard (option)</li> </ul>	
Expansion	<ul style="list-style-type: none"> <li>- 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface)</li> <li>- 1* M.2 B-key (3042, USB3.1 /USB2.0 interface W/SIM card slot)</li> <li>- TPM onboard (option)</li> </ul>	

Rear Panel I/O	<ul style="list-style-type: none"> <li>- 3* USB3.1 (Gen2)</li> <li>- 3* USB2.0</li> <li>- 2* HDMI</li> <li>- 2* RJ45</li> <li>- Line-out/MIC combo jack</li> <li>- 1* DC in</li> </ul>
Front Panel I/O	<ul style="list-style-type: none"> <li>- 1* Power SW, 1* Reset</li> <li>- 1* Power LED, 1* HDD LED</li> <li>- 1* MIC</li> <li>- 1* Line-out</li> <li>- 4* COM (COM1 support RS485)</li> <li>- 2* USB2.0</li> </ul>
Internal Connector	<ul style="list-style-type: none"> <li>- SIM Card Holder</li> </ul>
Power Source	<ul style="list-style-type: none"> <li>- Adapter : AC 90~240V input / DC12V_60W output</li> <li>- MB : DC12~24V input</li> </ul>
Compliance	<ul style="list-style-type: none"> <li>- CE, FCC, LVD, RoHS, ErP Ready</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>- System: 193 (W) x 142.4 (D) x 62 (H) mm</li> <li>- Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm</li> <li>- Net Weight: 2.2KG</li> <li>- Gross Weight: 3.5KG</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>- Operating Temperature: -20 ~ 60° C</li> <li>- (Under the condition of using M.2 interface SSD)</li> <li>- Operating Temperature: 0 ~ 50° C</li> <li>- (Under the condition of using 2.5" SATA HDD)</li> <li>- Storage Temperature: -20 ~ 85° C</li> <li>- Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul>
OS Support	<ul style="list-style-type: none"> <li>- Windows 11, Linux</li> </ul>